

# TD CUT

Small Countersunk Head

# Panelvit® TD CUT

FOR FIXING WINDOWS HARDWARE



Partially threaded screw with a **small head and 'CUT' crack-proof tip** suitable for fixing the components of fixing hardware systems for flap doors and windows.

**Head (Ø 7 mm) fits perfectly into the countersink** present in the hardware elements to be fixed.

**Smooth shank that does not interfere with the movement of the system**, even in screwing at an angle.



**Ø 4 mm thread guarantees a much higher tear resistance** than the common screws with Ø 3.5mm.

**'CUT' crack-proof tip** ideal for tightening close to the edges of the frame (angular movements, scissor supports, hinges), where the traditional screw may create splits that would compromise the grip of the fixture and the functioning of the system.

### CHROMITING® PROTECTIVE TREATMENT

This iridescent white treatment guarantees a **much better rust protection** than normal galvanisation treatments.

### LUBRICATION **LUBEX®**

MUSTAD antifriction treatment for **reducing fastening force by up to 50%**.



# Panelvit® TD CUT



CHROMITING® - LUBRICATED LUBEX®

CSK - Countersunk Head - PZ Recess



CE  
EN 14592 : 2009



Cod. Mustad	D (mm)	L tot (mm)	L fil (mm)	Dt (mm)	Pcs. 	Pcs. 
PZ2						
P1382A400300C8C	4	30	20	7	1000	9000
P1382A400350C8C	4	35	20	7	1000	7000

